


## TEMPCONTROL X-SERIE TEMPERATURFØLERE

### Handheld temperature sensor Type X12A



Hypodermic probe:  
Ø1,5 mm x L=130 mm, fast response.  
Maximum temperature 500 °C.  
Suitable for thermocouples only.

### Handheld temperature sensor Type X13/P13



Immersion probe:  
Ø3 mm x L=130 mm, general purpose probe.  
Maximum temperature 1000 °C (X13) and 450 °C (P13).  
Suitable for thermocouples as well as resistance thermometers.

### Handheld temperature sensor Type X15/P15



Air/Gas probe:  
Ø4 mm x L=130 mm with perforated tip.  
Maximum temperature 500 °C (X15) and 200 °C (P15).  
Suitable for thermocouples as well as resistance thermometers.

### Handheld temperature sensor Type X17



Surface probe:  
Ø8 mm x L=130 mm, fast response.  
Maximum temperature 900 °C.  
Suitable for thermocouples only.

### **Handheld temperature sensor Type X20/P20**



Insertion probe:

Ø3 mm x L=130 mm with pointed tip.

Maximum temperature 500 °C (X20) and 250 °C (P20)

Suitable for thermocouples as well as resistance thermometers.

### **Handheld temperature sensor Type X21**



Long immersion probe:

Ø6 x L=1000 mm for high temperature ovens.

Maximum temperature 1200 °C (Heatshield optional).

Suitable for thermocouples only.