

NEW! Moving your Control Forward – Variable Frequency Drives

Use our VFDs as a stand-alone product or integrated with our PLC+HMI controllers.



VFD: Easy to Program. Simple to Use.

- EMC built-in filters
- Variety of mounting options
- Temperature - extended operating range
- Modbus RTU fieldbus
- UL, TÜV-SÜD safety and CE certified
- Braking units - built-in
- Sensorless Vector and Torque control
- Heavy-duty overload capacity
- STO (Safe Torque Off)

Use as an All-in-One package

Program the VFD using the same programming software as our controllers: UniStream®, Vision™ and Samba™



VFD Specifications

		UMI-B1 EU	UMI-B1 UL	UMI-B5 UL
Power	Input Voltage	200-240VAC, Single Phase 380-440VAC, Three Phase	200-240VAC, Single Phase 200-240VAC, Three Phase 380-480VAC, Three Phase	200-240VAC, Three Phase 380-480VAC, Three Phase
	Input Frequency	50/60Hz		
	Supported Motors	Asynchronous Induction Motors, Three Phase Input		Asynchronous Induction Motors, Three Phase Input Permanent Magnet Synchronous Motors, Three Phase Input
	Output Frequency	0-400Hz		
	Overload Capacity	150%, 60 seconds 180%, 10 seconds 200%, 1 second		
Control	Control Method	SVPWM (Space Vector PWM) SVC (Sensorless Vector Control)		
	Control Setting	MODBUS, Analog, Digital, PID, Pulse		
	Communication	MODBUS RTU RS-485		
Input	Analog Inputs	Total 2: 1 input 0-10V, 0-20mA, 1 input 0-10V		Total 3: 2 inputs 0-10V, 0-20mA, 1 input 0-10V
	Digital Inputs	Total 5: 4 inputs 1kHz, 1 input 50kHz		Total 9: 8 inputs 1kHz, 1 input 50kHz
Output	Analog Outputs	Up to 2: 1 output 0-10V, 0-20mA ≤2.2kW/3HP, (2nd output available from >2.2kW/3HP)	2 outputs 0-10V, 0-20mA	
	Digital Outputs	1 output sink/source		Total 2: 1 output sink/source, 1 output 50kHz
	Relay Outputs	Up to 2: 1 Programmable Multi-functional output. 2nd output available from >2.2kW/3HP	Total 2 Programmable Multi-functional outputs	
Features	Dynamic Braking Unit	Built-in (≤37kW/50HP) Optional (>37kW/50HP)		Built-in (≤30kW/40HP) Optional (>30kW/40HP)
	EMC Filters	Built-In C3 (≥4kW/5HP), Comply with IEC/EN 61800-3 Optional C3 (<4kW/5HP), Comply with IEC/EN 61800-3		Built-In C3, Comply with IEC/EN 61800-3
		Optional C2, Comply with IEC/EN 61800-3		
General	Operating Temperature	(-10)°C/14°F – 50°C/122°F (de-rated by 1% for every 1°C/2°F above 40°C/104°F)		
	Altitude	2000m/6600 ft (de-rated by 1% for every additional 100m/330ft above 1000m/3300ft)		
	Enclosure Rating	IP20		
	Mounting Options	Wall and Rail (≤2.2kW/3HP)		Wall, Flange
		Wall and Flange (>2.2kW/3HP)		
	Cooling	Air-cooling		
	Safe Torque Off	√	×	
Compliance	CE, TÜV-SÜD Safety Mark		CE, UL and cUL	

VFD Models

UMI-B1 Series - ST0



Article Number	Input Voltage	Rated Output Power		Rated Input Current (A)	Rated Output Current (A)	Dimensions (W x H x D mm)			Safety Class
		kW	HP						
UMI-0004BE-B1	Single phase 200-240V	0.4	0.5	6.5	2.5	80	160	124	Class SIL2 PLd CAT.3
UMI-0007BE-B1		0.75	1	9.3	4.2	80	160	124	
UMI-0015BE-B1		1.5	2	15.7	7.5	80	185	141	
UMI-0022BE-B1		2.2	3	24	10	80	185	141	
UMI-0007EE-B1		0.75	1	3.4	2.5	80	185	141	
UMI-0015EE-B1	1.5	2	5	4.2	80	185	141		
UMI-0022EE-B1	2.2	3	5.8	5.5	80	185	141		
UMI-0040EE-B1	4	5	13.5	9.5	146	256	167	Class SIL3 PLd CAT.3	
UMI-0055EE-B1	5.5	7.5	19.5	14	146	256	167		
UMI-0075EE-B1	7.5	10	25	18.5	170	320	197		
UMI-0110EE-B1	11	15	32	25	170	320	197		
UMI-0150EE-B1	15	20	40	32	170	320	197		
UMI-0185EE-B1	18.5	25	47	38	200	341	185		
UMI-0220EE-B1	22	30	51	45	200	341	185		
UMI-0300EE-B1	30	40	70	60	250	400	202		
UMI-0370EE-B1	37	50	80	75	250	400	202		
UMI-0450EE-B1	45	60	98	92	282	560	238		
UMI-0550EE-B1	55	75	128	115	282	560	238		
UMI-0750EE-B1	75	100	139	150	282	560	238		
UMI-0900EE-B1	90	120	168	180	338	554	330		
UMI-1100EE-B1	110	150	201	215	338	554	330		

UMI-B1 Series - UL



Article Number	Input Voltage	Rated Output Power		Rated Input Current (A)	Rated Output Current (A)	Dimensions (W x H x D mm)		
		kW	HP					
UMI-0004BU-B1	Single phase 200-240V	0.4	0.5	6.5	2.5	80	160	124
UMI-0007BU-B1		0.75	1	9.3	4.2	80	160	124
UMI-0015BU-B1		1.5	2	15.7	7.5	80	185	141
UMI-0022BU-B1		2.2	3	20	10	80	185	141
UMI-0004CU-B1	Three phase 200-240V	0.4	0.5	3.7	2.5	80	185	141
UMI-0007CU-B1		0.75	1	5	4.2	80	185	141
UMI-0007EU-B1	Three phase 380-480V	0.75	1	3.4	2.5	80	185	141
UMI-0015EU-B1		1.5	2	5	4.2	80	185	141
UMI-0022EU-B1		2.2	3	5.8	5.5	80	185	141

UMI-B5 Series - UL



Article Number	Input Voltage	Rated Output Power		Rated Input Current (A)	Rated Output Current (A)	Dimensions (W x H x D mm)			
		kW	HP						
UMI-0007CU-B5	Three phase 200-240V	0.75	1	5	4.5	126	193	175	
UMI-0015CU-B5		1.5	2	7.7	7	146	263	181	
UMI-0022CU-B5		2.2	3	11	10	146	263	181	
UMI-0040CU-B5		4	5	17	16	170	332	216	
UMI-0055CU-B5		5.5	7.5	21	20	170	332	216	
UMI-0075CU-B5		7.5	10	31	30	230	342	216	
UMI-0110CU-B5		11	15	43	42	255	407	245	
UMI-0150CU-B5		15	20	56	55	255	407	245	
UMI-0185CU-B5		18.5	25	71	70	270	555	325	
UMI-0220CU-B5		22	30	81	80	270	555	325	
UMI-0300CU-B5		30	40	112	110	270	555	325	
UMI-0370CU-B5		37	50	132	130	325	680	365	
UMI-0450CU-B5		45	60	163	160	325	680	365	
UMI-0550CU-B5		55	75	200	200	325	680	365	
UMI-0015EU-B5		Three phase 380-480V	1.5	2	5	3.7	126	193	175
UMI-0022EU-B5			2.2	3	5.8	5	126	193	175
UMI-0040EU-B5	4		5	13.5	9.5	146	263	181	
UMI-0055EU-B5	5.5		7.5	19.5	14	146	263	181	
UMI-0075EU-B5	7.5		10	25	18.5	170	332	216	
UMI-0110EU-B5	11		15	32	25	170	332	216	
UMI-0150EU-B5	15		20	40	32	230	342	216	
UMI-0185EU-B5	18.5		25	47	38	230	342	216	
UMI-0220EU-B5	22		30	56	45	255	407	245	
UMI-0300EU-B5	30		40	70	60	255	407	245	
UMI-0370EU-B5	37		50	80	75	270	555	325	
UMI-0450EU-B5	45		60	94	92	270	555	325	
UMI-0550EU-B5	55		75	128	115	270	555	325	
UMI-0750EU-B5	75		100	160	150	325	680	365	
UMI-0900EU-B5	90		120	190	180	325	680	365	
UMI-1100EU-B5	110		150	225	215	325	680	365	

Optional Parts




External Keypads



Flange Mounting Plates



Braking Resistors



C3 Input Filters
C2 Filters

Product Designation Key

UMI - 0022	E	U	- B1
①	②	③	④ ⑤

No.	Key	Description
①	Product Line	Unitronics Motion Inverters
②	Power Range	0004:400W/0.5HP 0022:2.2kW/3HP
③	Power Rating	B: 1PH 200V-240V C: 3PH 200V-240V E: 3PH 380V-440V/480V
④	Certification	U - UL Certified E - TÜV-SÜD Certified
⑤	Product series	B1 / B5

